




Code	A mm	B mm	C mm
TPRCS 3000x50	190	56	88
TPRCS 3000x80	220	86	118

Code	Smax mm	Max. punching force	Gas spring force		Gas spring model	ISO VDI	Max. working specs		Max. width of driver	Kg
			Initial daN	Final daN			Velocity	Strokes / min		
TPRCS 3000x50-1	50	3000 daN	400	≈ 600	TPK 32x50 YW	✓	0,5 m/s	40 spm	35 mm	9,2
TPRCS 3000x50-2			200	≈ 270	TPS 32x50.2 YW					
TPRCS 3000x50-3			350	≈ 520	MICRO32VSx50 YW					
TPRCS 3000x80-1	80	3000 daN	400	≈ 600	TPK 32x80 YW	✓	0,5 m/s	35 spm	35 mm	10,0
TPRCS 3000x80-2			200	≈ 270	TPS 32x80.2 YW					
TPRCS 3000x80-3			350	≈ 520	MICRO32VSx80 YW					

### Working force distribution



Maximum force that can be applied to the punch depending on eccentricity, so that the stress in the assembly is the same as it was when the punch was completely centred.

### How to order

TPRCS 3000 x 50 - 1

Code    Stroke    Gas spring model

TPK 32    TPS 32.2    MICRO 32VS

### Maximum inclination

